






Case System RI 25 SLC

Color-TV-camera for inspections from DN 30 – 150 (ID 1.2" – 6")
 Bendable 87° from DN 40 (ID 1.6")

Art- No	Name	Article
79115	<ul style="list-style-type: none"> • stainless steel camera housing with flexible spring connection, camera \varnothing 25 mm, length 29,5 mm • waterproof up to 1 bar • high resolution color-camera-module with electronical shutter • LED-lighting • wide angle lens with sapphire protection • fix focus from 3 cm • 25 m (80 ft) push cable 6,5 mm in diameter on rotating reel basket • TFT-monitor 5.6" • meter counter displayed on the monitor • SD-memory card-slot for saving single pictures or video sequences • easy handling with integrated buttons • battery with charger and charge indication • video-out BNC • transport case • mains power from 100V AC up to 240V AC or with built-in battery (ca. 4 h) 	 <p>Extension example</p>

Options/Accessories:


70193	guide ball 40 <ul style="list-style-type: none"> • screwable in two parts • diameter 40 mm • bendable 87° from DN 50 (ID 2') 	
70192	guide brush <ul style="list-style-type: none"> • screwable in two parts • bendable 87° from DN 70 (ID 2.8") 	
53165	text-generator for RI 1320, RI 2020, RI 25 SLC & RI 25 VB SLC <ul style="list-style-type: none"> • free text • date and time • display of the meters, set of meters • 100 fix lines and 10 fix pages • keyboard with protective cover for outdoor use 	
77033	locator sonde (without receiver) <ul style="list-style-type: none"> • usable between push cable and camera head • with coil and transmitter circuit board, frequency 512 Hz 	

79013	locator sonde (without receiver) <ul style="list-style-type: none"> • usable between push cable and camera head • with coil and transmitter circuit board, frequency 33 kHz 	
-------	--	---



Case System RI 25 VB SLC


Color-TV-camera for inspections from DN 30 – 150 (ID 1.2"– 6")
 Bendable 87° from DN 40 (ID 1.6")

Art- No	Name	Article
79116	<ul style="list-style-type: none"> • stainless steel camera housing with flexible spring connection, camera ø 25 mm, length 36,5 mm • waterproof up to 1 bar • high resolution color-camera-module with electronical shutter and correctly positioned image (VB) • LED-lighting • wide angle lens with sapphire protection • fix focus from 3 cm • 25 m (80 ft) push cable 6,5 mm in diameter on rotating reel basket • TFT-monitor 5.6" • meter counter displayed on the monitor • SD-memory card-slot for saving single pictures or video sequences • easy handling with integrated buttons • battery with charger and charge indication • video-out BNC • transport case • mains power from 100V AC up to 240V AC or with 	 <p>Extension example</p>




Case System RI 1320 SLC

Color-TV-camera for inspections from DN 15 – 40 (ID 0.6" – 1.6")
 Bendable 87° from DN 25 (ID 1")

Art- No	Name	Article
30623	<ul style="list-style-type: none"> • stainless steel camera housing with flexible spring connection, camera \varnothing 13 mm, length 24,6 mm • waterproof up to 1 bar • high resolution color-camera-module with electronical shutter • LED-lighting • wide angle lens with sapphire protection glass • fix focus from 3 cm • 20 m (66 ft) push cable 3 mm in diameter on rotating reel basket • TFT-monitor 5.6" • meter counter displayed on the monitor • SD-memory card-slot for saving single pictures or video sequences • easy handling with integrated buttons • battery with charger and charge indication • video-out BNC • transport case • mains power from 100V AC up to 240V AC or with built-in battery (ca. 4 h) 	 <p>Extension example</p>

Options/Accessories:

88009	guide ball 20 <ul style="list-style-type: none"> • screwable in two parts • diameter 20 mm • bendable 87° from DN 25 (ID 1") 	
53165	text-generator for RI 1320, RI 2020, RI 25 SLC & RI 25 VB SLC <ul style="list-style-type: none"> • free text • date and time • display of the meters, set of meters • 100 fix lines and 10 fix pages • keyboard with protective cover for outdoor use 	